

- PREPARE SOIL BEFORE INSTALLING BLANKETS, INCLUDING ANY NECESSARY APPLICATION OF LIME, FERTILIZER, AND SEED. NOTE: WHEN USING CELL-O-SEED DO NOT SEED PREPARED AREA. CELL-O-SEED MUST BE INSTALLED WITH PAPER SIDE DOWN.
 BEGIN AT THE TOP OF THE SLOPE BY ANCHORING THE BLANKET IN A 6" (15cm) DEEP X 6" (15cm) WDE TRENCH WITH APPROXIMATELY 12" (30cm) OF BLANKET EXTENDED BEYOND THE UP-SLOPE PORTION OF THE TRENCH. ANCHOR THE BLANKET WITH A ROW OF STAPLES/STAKES APPROXIMATELY 12" (30cm) APART IN THE BOTTOM OF THE TRENCH. ANCHOR THE BLANKET THE TRENCH AFTER STAPLING. APPLY SEED TO COMPACTED SOIL AND FOLD REMAINING 12" (30cm) PORTION OF BLANKET BACK OVER SEED AND COMPACTED SOIL. SECURE BLANKET OVER COMPACTED SOIL WITH A ROW OF STAPLES/STAKES SPACED APPROXIMATELY 12" (30cm) APART ACROSS THE WOTH OF THE BLANKET.
 ROLL THE BLANKETS (A.) DOWN OR (B.) HORIZONTALLY ACROSS THE SLOPE. BLANKETS WILL UNROLL WITH APPROPRIATE SIDE AGAINST THE SOIL SURFACE. ALL BLANKETS MUST BE SECURELY FASTENED TO SOIL SURFACE BY PLACING STAPLES/STAKES IN APPROPRIATE LOCATIONS AS SHOWN IN THE STAPLE PATTERN GUIDE. WHEN USING OPTIONAL DOT SYSTEM, STAPLES/STAKES SHOULD BE PLACED THROUGH EACH OF THE COLORED DOTS CORRESPONDING TO THE APPROPRIATE STAPLE PATTERN.
 THE EDGES OF PARALLEL BLANKETS MUST BE STAPLED MITH APPROXIMATELY 2"-5" (5cm-12.5cm) OVERLAP DEPENDING ON BLANKET TYPE. TO ENSURE PROPER SEAM ALIGNMENT, PLACE THE EDGE OF THE OVERLAPPING BLANKET.
 CONSECUTIVE BLANKETS SHOW INT THE SLOPE AWENT BE NUST BE DAD OVER LAPPING BLANKET.
 CONSECUTIVE BLANKETS SPLICED DOWN THE SLOPE AND STAPLE PROVINGATEL STAPLE DATTERN.
 THE EDGES OF PARALLEL BLANKETS MUST BE SLOPE MUST BE PLACED FOR DEVERLAPPING BLANKET.
 CONSECUTIVE BLANKETS SPLICED DOWN THE SLOPE AWENT, PLACE THE EDGE OF THE OVERLAPPING BLANKET.
 CONSECUTIVE BLANKETS SPLICED DOWN THE SLOPE AWENT, PLACE THE DEDG OF THE OVERLAPPING BLANKET.
 CONSECUTIVE BLANKETS SPLICED DOWN THE SLOPE AW

- 3" (7. WDTH
- 6. FOLLOW MANUFACTURER'S RECOMMENDED STAPLE PATTERN, FOR THE SLOPE FOR THE SPECIFIED BLANKET.

NOTE:

IN LOOSE SOIL CONDITIONS, THE USE OF STAPLE OR STAKE LENGTHS GREATER THAN 6" (15cm) MAY BE NECESSARY TO PROPERLY SECURE THE BLANKETS.

611 - STANDARD STAPLE PATTERN 611 - Std Staple Pattern.dwg 5/2015

$H: Cad_Comn Details Updated 0 - EROSION 611 - Std Staple Pattern$		
CITY OF BLOOMINGTON MINNESOTA 1700 W 98TH ST. BLOOMINGTON NM 55431 PHONE (952) 563-8700	PLATE NAME: 611 — Std Staple Pattern	
ENGINEERING DIVISION	LAST REVISED: 5/15/2015	
PUBLIC WORKS DEPARTMENT	LAST REVISED BY: KBO	