

- 1. ALL TRAFFIC CONTROL DEVICES, INSTALLATION AND SIGNING SHALL CONFORM TO THE LATEST VERSION OF THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MMUTCD).
- 2. WOOD POSTS SHALL BE TREATED PER MNDOT SPECIFICATION 3491 WITH COPPER NAPHTHENATE OR BORATE. ARSENIC CONTAINING PRESERVATIVES SHALL NOT BE USED. FIELD APPLICATION OF PRESERVATIVES WILL BE ALLOWED ONLY FOR TREATMENT OF INSIDE OF 1" DIA HOLES.
- 3. 1" DIA HOLES SHALL BE DRILLED, ON CENTER, IN EACH FACE OF WOOD POST AS SHOWN IN DETAIL ABOVE.
- 4. BACKFILL MATERIAL AROUND WOOD POST SHALL BE COMPACTED TO THE SATISFACTION OF THE ENGINEER.

702 - SIGN (GROUND MOUNT.-WOOD) 702 - SIGN (GROUND MOUNT.-WOOD).DWG 9/2016

H:\Cad_Comn\Details Updated\0 - 700 - TRAFFIC complete\702 - Sign (Ground Mount.-Wood)

PLATE NAME:

BLOOMINGTON MINNESOTA

1700 W 98TH ST. BLOOMINGTON MN 55431 PHONE (952) 563-8700

702 - Sign (Ground Mount.-Wood)

ENGINEERING DIVISION
PUBLIC WORKS DEPARTMENT

LAST REVISED: 9/16/2016
LAST REVISED BY: KBO